SAMSUNG

The power to perfect professionals

Productive, precise, powerful. Samsung introduces a new benchmark for high resolution. Featuring Samsung Matte Display technology, Samsung ViewFinity monitors are designed to unlock the potential of business professionals, content creators and graphic designers.



Conquer precision work with ease.

Deeper details for creative clarity

With UHD 4K resolution, every detail is viewed in enhanced depth, while IPS panels deliver exceptional color quality and wide viewing angles of 178°.

Pro-level color expression

The S80PB series features an extended color range supporting up to 98% of DCI-P3, creating richer and more vibrant colors in every project. It's pro-level precision for graphic designers and other discerning users.

Realize richer, more refined shades

Show more with every shade. HDR support brings a true high dynamic range of luminous blacks and whites to the screen. Dark areas are richer and more profound, while bright parts are even more dazzling and intense, delivering clear and detailed resolution for an outstanding viewing experience.



Easily connected, instantly productive

An ultimate hub for versatile use

Ditch the clutter. You can power your laptop and transmit data with just one USB Type-C cable with 90W charging. And the LAN port allows a laptop to connect to the monitor for Ethernet use.

Make room for more tasks

With PBP, you can view input from two simultaneous sources, to review two projects or run two programs at once. Use PIP to resize a second source to up to 25% of the screen, to work on one task while monitoring another.



User-friendly comfort

Experience glare-free productivity in any lighting environment with the world's first UL-certified Matte Display.


Edit and review content clearly even in bright daylight. The UL-certified glare-free monitor enables professionals to review and edit at consistent levels of brightness and color, even without a monitor hood.

Ergonomic design

Pivot the screen from portrait to landscape or adjust up and down for the perfect height. Then tilt and swivel to capture the best viewing angle.

Relieve your eyes from strain

Keep your eyes fresh and strainfree. During late-night projects, brightness and color temperature adjust automatically for optimization in any environment. TUV-certified for intelligent eye care, Samsung protects eyes against excessive blue light with Eye Saver Mode and Flicker Free technology.



ViewFinity S8 High Resolution Monitor S80PB Series

nterface	Screen Size Flat / Curved Active Display Size (H x V) Panel Type (PLS / VA / TN) Aspect Ratio Brightness Contrast Ratio (Static) Contrast Ratio (Bynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	S278804PXN 27" Flat 23.5" x 13.2" (596.7 x 335.6mm) IPS 16-9 350 nits (Typ.) 320 nits (Min) 1000-1 (Typ.) Mega \times DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178" / 178" 14.7M 16.7M 16	\$32B804PXN 32" Flat 27.5" x 15.4" (697.3 x 392.2mm) IPS 16:9 350 nits (Typ) / 280 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
	Flat / Curved Active Display Size (H x V) Panel Type (PLS / VA / TN) Aspect Ratio Brightness Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	Flat 23.5" x 13.2" (596.7 x 335.6mm) IPS 16:9 350 nits (Typ.) / 320 nits (Min) 1000:1 (Typ.) Mega & DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	Flat 27.5" x15.4" (697.3 x 392.2mm) IPS 16:9 350 nits (Typ.) / 280 nits (Min) 1000:1 (Typ.) Mega © DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
terface	Active Display Size (H x V) Panel Type (PLS / Va / TN) Aspect Ratio Brightness Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	23.5" x 13.2" (596.7 x 335.6mm) IPS 16:9 350 nits (Typ) / 320 nits (Min) 1000-1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	2.75" x 15.4" (697.3 x 392.2mm) IPS 16:9 350 nits (Typ) / 280 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
terface	Panel Type (PLS / VA / TN) Aspect Ratio Brightness Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	IPS 16:9 350 nits (Typ) / 320 nits (Min) 1000:1 (Typ.) Mega © DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	IPS 16:9 350 nits (Typ) / 280 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
terface	Aspect Ratio Brightness Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	16:9 350 nits (Typ) / 320 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	16:9 350 nits (Typ) / 280 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
terface	Brightness Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	350 nits (Typ) / 320 nits (Min) 1000:1 (Typ.) Mega ∞ DCR 4 K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	350 nits (Typ) / 280 nits (Min) 1000-1 (Typ.) Mega ∞ DCR 4K / UHD (SR404 x 2160) 5 ms (GTG)
terface	Contrast Ratio (Static) Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	1000:1 (Typ.) Mega & DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	1000:1(Typ.) Mega ∞ DCR 4K/UHD (3840 x 2160) 5 ms (GTG)
terface	Contrast Ratio (Dynamic) Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG) 178° /178°	Mega ∞ DCR 4K / UHD (3840 x 2160) 5 ms (GTG)
nterface	Resolution Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	4K / UHD (3840 x 2160) 5 ms (GTG) 178° / 178°	4K / UHD (3840 x 2160) 5 ms (GTG)
nterface	Response Time Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	5 ms (GTG) 178° / 178°	5 ms (GTG)
nterface	Viewing Angle (H/V) Color Support Color Gamut (NTSC 1976)	178° / 178°	
nterface	Color Support Color Gamut (NTSC 1976)		
terface	Color Gamut (NTSC 1976)		178° / 178°
terface			16.7M
nterface		72%	72%
nterface	Refresh Rate	60Hz	60Hz
nterface	Anti-Glare	25%	25%
	DisplayPort	Yes (Version 1.4)	Yes (Version 1.4)
	HDMI	Yes (Version 2.2)	Yes (Version 2.2)
	Headphone	Yes	Yes
	USB-C Port	Yes	Yes
	USB-C Power Delivery	90W	90W
	USB Hub	3.0 x3	3 (3.0)
Features	Eye Saver Mode	Yes	Yes
	Flicker Free	Yes	Yes
	Picture-In-Picture	Yes	Yes
	Picture-By-Picture	Yes	Yes
	Game Mode	Yes	Yes
	Image Size	Yes	Yes
	Windows Certification	Windows 10	Windows 10
	Eco Saving Plus	Yes	Yes
	Off Timer Plus	Yes	Yes
	Auto Source Switch	Yes	Yes
	Other	Adaptive Picture, Eco Light Sensor, Eco Sensor Mode	Adaptive Picture, Eco Light Sensor, Eco Sensor Mode
Operation	Temperature	50° –104° (10~40°C)	10~40 °C
	Humidity	10 ~ 80% (Non-condensing)	10~40 C 10~80% (Non-condensing)
Conditions Calibration	Factory Tuning	Yes	Yes
	ractory running	Custom, High Bright, sRGB, BT.709, DCI-P3, DICOM Simulation, Cinema,	Custom, High Bright, sRGB, BT.709, DCI-P3, DICOM Simulation, Cinema,
	Color Mode	Dynamic Contrast	Dvnamic Contrast
	Footon Colibertion Bonnet	Yes	Yes
D	Factory Calibration Report Color	Black	Black
esign		HAS	
	Stand Type		HAS
	HAS (Height Adjustable Stand)	120.0mm(±5.0mm)	120.0mm(±5.0mm)
	Tilt	-2.0°(±2.0°)~25.0°(±2.0°)	-2.0°(±2.0°)-25.0°(±2.0°)
	Swivel	-30.0°(±2.0°)~30.0°(±2.0°)	-30.0°(±2.0°)~30.0°(±2.0°)
	Pivot	-2.0°(±2.0°)~92.0°(±2.0°)	-2.0°(±2.0°)-92.0°(±2.0°)
	Wall Mount (VESA)	100 x 100mm	100 x100
	Recycled Plastic	Over 3%	Over 3%
	Eco Sensor	Yes	Yes
Power	Power Supply	AC100~240V	AC100~240V
	Туре	Internal Power	Internal Power
Dimensions	Set Dimension without Stand	24.2" x14.5" x1.7"	28.2" x16.5" x 2.1"
	(W x H x D)	24.2 A 14.3 A 1./	20.2 A 10.3 A 2.1
	Set Dimension with Stand	24.2" x 21.7" x 7.7"	28.2" x 24.0" x 8.9"
	(WxHxD)		
	Package Dimension (W x H x D)	27.0" x 6.7" x 17.7"	31.9" x 7.6" x 21.4"
Weight	Set Weight without Stand	10.4 lbs.	12.1 lbs.
	Set Weight with Stand	14.8 lbs.	17.9 lbs.
	Package Weight	18.5 lbs.	23.4 lbs.
Accessory	Power Cable Length	Yes (1.5 m)	Yes (1.5 m)
	HDMI Cable	Yes	Yes
	DP Cable	Yes	Yes
	USB-C Cable (C to C)	Yes	Yes
Managara			
Varranty	Warranty	3 Years	3 Years
Certifications and Safety	Energy Star	Yes, v.8.0	Yes, v.8.0

Connectivity

1. Power 4. USB-C

2. HDMI In 5. LAN

3. DisplayPort In 6. Headphone In





7. USB / Service

8. USB 3.0











Contact your Connection Account Team for more information.

 Business Solutions
 Enterprise Solutions
 Public Sector Solutions

 1.800.800.0014
 1.800.369.1047
 1.800.800.0019

www.connection.com/Samsung

SAMSUNG

@2022 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All brand, product, service names and logos are trademarks of their respective manufacturers and companies. Simulated screen images. Non-metric weights and measurements are approximate. Specifications and design are subject to change without notice. See samsung.com for detailed information. Printed in USA. MON-S80PB-DSHT-NOV22TK